

## OMNITRONIC XKB-215A 2-way Speaker, active, DSP

Active speaker with 15" woofer, 1.75" driver, 60 W RMS HF, 300 W RMS LF

Art. No.: 11038796

GTIN: 4026397606492



### Features:

- Active PA speaker system for touring applications and permanent installations
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 38 cm woofer and 4 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Digital signal processor
- DSP presets: LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
- Control via Bluetooth
- LCD display
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- For application areas such as: Mobile use; rental; sports centres/gyms; mobile djs / entertainer

### Logistic

EAN / GTIN: 4026397606492

Weight: 22,55 kg

Length: 0.52 m

Width: 0.43 m

Height: 0.77 m

### Technical specifications:

|                    |                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------|
| Power supply:      | 230 V AC, 50 Hz                                                                                  |
| Power consumption: | Max. 800 W                                                                                       |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |

|                       |                                                                                                     |
|-----------------------|-----------------------------------------------------------------------------------------------------|
| Power:                | Program: 600W<br>Rated: 60W RMS HF<br>Rated: 300W RMS LF                                            |
| Frequency range:      | 50 - 20000 Hz                                                                                       |
| Sensitivity:          | 96 dB                                                                                               |
| Max. SPL:             | 121 dB                                                                                              |
| DSP:                  | Digital signal processor                                                                            |
| DSP presets:          | LIVE; MUSIC; SPEECH; DJ; TRIPOD;<br>MONITOR; WALL                                                   |
| Dispersion angle:     | 90° x 50°                                                                                           |
| Control:              | Bluetooth                                                                                           |
| Attachment system:    | Flange: Ø 35mm                                                                                      |
| Circuitry:            | Class D Biamp                                                                                       |
| Display type:         | LCD display                                                                                         |
| Control elements:     | Encoder, Master control                                                                             |
| Controls:             | Limiter                                                                                             |
| Status LED:           | Power, signal, limit                                                                                |
| Connections:          | Output: line via 1 x 3-pin XLR                                                                      |
| Input channels:       | 2 x mono with mic-line switch via Combination<br>socket (XLR/jack), channel control via rotary dial |
| Equalizer:            | Master: 1 x 3-band tone control                                                                     |
| Speaker:              | 1 x woofer 15"<br>Voice coil compression tweeter highs 1.75"                                        |
| Type of speaker:      | Compact cabinet speaker                                                                             |
| Type of construction: | Vented                                                                                              |
| Carrying handle:      | 3 pc/pcs                                                                                            |
| Dimensions:           | Width: 37 cm<br>Depth: 45 cm<br>Height: 70 cm                                                       |
| Weight:               | 20.95 kg                                                                                            |

## Scope of delivery:

1 x top  
 1 x user manual  
 1 x power cord  
 1 x declaration of conformity