

OMNITRONIC AS-500 Active system

Powerful compact active PA system, 500 W RMS

Art. No.: 11038808

GTIN:



The article is no longer in our assortment.

Features:

- Mobile subwoofer/satellite system with class D circuitry
- Provides perfect sound and good level stability in various kinds of mobile PA applications up to medium-sized party events - ideal for solo entertainers, small bands and mobile discos
- Several active systems can be used to set up large PA systems
- 30 cm subwoofer in bassreflex cabinet provides powerful, dry bass
- Tops with 16.5 cm bass-midrange speakers and 2.5 cm neodymium driver system
- Balanced inputs via combo jacks (XLR/6.3 mm) and XLR parallel outputs
- Microphone input (combo XLR/6.3 mm jack)
- Aux input (3.5 mm jack/RCA), ideal for portable music players (e.g. iPod)
- Adjustable volume balance between satellites
- Adjustable crossover frequency for subwoofer and satellites
- 5-band equalizer for fine-tuned sound of the master signal
- Stereo/mono selection
- Phase switchable for subwoofer
- Groundlift switch against humming
- MDF enclosure with scratch-resistant lacquer surface, impact-resistant steel grille and flange for speaker distance tube
- Complete protection set against short-circuit, overheat, overload and overcurrent
- PowerCon input, power cable included
- Delivery includes two speaker cables
- Wheel board for easy transportation optionally available
- Wheelboard optional

Logistic

Technical specifications:

| | |
|-------------------------|---|
| Power consumption: | 600,00 W |
| Speaker: | 1 x woofer 12" |
| Transport aid: | Wheelboard optional |
| Weight: | 47 kg |
| Power supply: | 230 V AC, 50 Hz |
| Power output sine: | |
| Subwoofer: | 300 W RMS |
| Satellite speakers: | 2 x 100 W RMS |
| Components: | |
| Subwoofer: | 30 cm woofer (12") |
| Satellite speakers: | 2 x 16.5 cm woofer (6.5"), 2 x 2.5 cm neodymium tweeter (1") |
| Sensitivity: | |
| Subwoofer: | 95 dB |
| Satellite speakers: | 93 dB |
| Maximum SPL: | |
| Subwoofer: | 122 dB |
| Satellite speakers: | 112 dB |
| Frequency range: | |
| Subwoofer: | 35-140 Hz |
| Satellite speakers: | 140-20000 Hz |
| Inputs: | |
| Line: | combination XLR/6.3 mm jack L/R |
| Aux: | 3.5 mm jack/stereo RCA |
| Mic: | combination XLR/6.3 mm jack |
| Outputs: | |
| Line: | XLR L/R (feed-through output) |
| Speaker: | 2 x Speaker, 8 ohms |
| Protection circuits: | Short-circuit, overheat, overload, overcurrent |
| Dimensions (L x W x H): | |
| Subwoofer: | 552 x 375 x 444 mm |
| Satellite speakers: | 233 x 231 x 318 mm |