

OMNITRONIC ACS-600 Active System

Active mobile column PA system with 3-channel mixer, 600 W

Art. No.: 11038865

GTIN: 4026397543872



The article is no longer in our assortment.

Features:

- 600-watt mobile column PA system for DJs and musicians
- Convinces with excellent speech reproduction and wide coverage
- Flexible use: mono, 2.1 or stereo setup with 2 systems linked together
- Smart click mechanism allows stacking satellites in mono mode without cables
- 1 active 2 x 25 cm bassreflex subwoofer (2 x 10")
- 2 fullrange satellites with 6 x 6.5 cm drivers (2.5")
- 130 dB max. SPL (peak)
- 2-channel amplifier system with 1 x 400 W for subwoofer and 2 x 100 W or 1 x 200 W for satellites
- Efficient class D circuitry
- Integrated 3-channel mixer
- 1 mono input (combination XLR/6.3 mm jack), switchable mic/line
- 1 stereo input (RCA, 3.5 mm jack)
- 1 stereo input (2 x combination XLR/6.3 mm jack)
- Volume control per channel, balance, subwoofer and master control
- Record and feed-through outputs (XLR)
- Durable wooden cabinets with protective metal grills
- Subwoofer with convenient compartment for satellites, castors and M20 metal flange
- Set incl. 2 speaker cables for 2.1 setup and 2 bags for the satellites
- Castors

Logistic

EAN / GTIN: 4026397543872

Weight: 51,40 kg

Length: 0.71 m

Width: 0.48 m

Height: 0.88 m

Bulky product

Technical specifications:

Power supply: 115/230 V AC, 50/60 Hz

Power consumption:	120 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	45 - 160 Hz
Speaker:	1 x woofer 10"
Transport aid:	Castors
Dimensions:	Width: 70,5 cm Depth: 37 cm Height: 76 cm
Weight:	46 kg
Subwoofer:	
Power output:	400 W at 4 ohms 2 x 100 W at 8 ohms
Woofer:	2 x 25 cm (2 x 10")
Maximum SPL:	125 dB
Dimensions (L x W x H):	705 x 370 x 760 mm (incl. wheels)
1 satellite:	
Power output:	100 W at 8 ohms
Driver:	6 x 6.5 cm (6 x 2.5")
Maximum SPL:	125 dB
Dispersion angle	90° x 10°/-45°
Dimensions (L x W x H):	100 x 107 x 718 mm
2 satellites:	
Power output:	200 W at 8 ohms
Driver:	12 x 6.5 cm (12 x 2.5")
Maximum SPL:	130 dB
Dispersion angle:	90° x 60°
Dimensions (L x W x H):	100 x 107 x 1436 mm
Inputs:	
Mic/Line 1:	combination XLR/6.3 mm jack
Line 2:	RCA L/R, 3.5 mm jack
Mic/Line 3:	2 x combination XLR/6.3 mm jack
Speaker outputs:	2 x speaker
Rec/Thru:	2 x XLR