

OMNITRONIC LI-206W MK2 2-Way Top

Speaker with mount, 6.5" woofer, 1" dome tweeter, 50 W RMS

Art. No.: 11038987

GTIN: 4026397493948



Features:

- Dedicated full-range bassreflex system for fixed installation
- 16.5 cm (6.5") bass speaker and 25 mm (1") horn tweeter, with PTC tweeter protection
- Attractive trapezoidal cabinet made of 8/12 mm plywood
- Scratch-resistant lacquer surface in black or white
- Supplied with movable mounting bracket for ceiling or wall installation
- Impact-resistant steel grille with acoustic foam
- 2 x M10 thread inserts
- For PA applications in restaurants, bars, discos and shops
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Logistic

EAN / GTIN: 4026397493948

Weight: 5,00 kg

Length: 0.21 m

Width: 0.21 m

Height: 0.35 m

Technical specifications:

Power:	Program: 100W Rated: 50W RMS
Frequency range:	80 - 20000 Hz
Sensitivity:	89 dB
Max. SPL:	109 dB
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Crossover frequency:	2200 Hz
Speaker:	1 x woofer 6.5"

Type of speaker:	On ceiling/on wall speaker
Color:	White
Dimensions:	Width: 20 cm Depth: 20 cm Height: 32 cm
Weight:	4.70 kg
Components:	16.5 cm woofer (6.5"), 2.5 cm calotte (1")
Connection:	2-pole plug-in screw terminal
Dispersion angle:	120°

Scope of delivery:
