

OMNITRONIC MAXX-1206DSP 2.1 Active System

Art. No.: 11039060

GTIN: 4026397729498



List price: 712.81 €

incl. 19% VAT.

Features:

- For application areas such as: Mobile use; mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels
- <p>OMNITRONIC MAXX-1206 2-Way Top 6.5" 2x
- <p class="featureSatz">2 x 6.5" passive full-range speaker, 100 W RMS
- 2-way bass-reflex system with 6.5" bass-midrange speaker and 1" titanium compression driver
- Serve as a mobile 2.1 system together with the MAXX-1206 subwoofer
- With passive 2-way crossover, PTC tweeter protection
- With rigging points
- Black metal grille with acoustic foam
- Rugged carrying handle
- 2 pieces per set
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- Application possibility: Standing; suspended; monitoring; on stand

Package contents

- 2 x top, 2 x speaker cable
- <p>OMNITRONIC MAXX-1206DSP 2.1 Active Subwoofer 12"
- <p class="featureSatz">High-power 12" active subwoofer with DSP and Bluetooth, 450 watts
- 12" subwoofer with Class D amplifier in bassreflex cabinet
- Amplifier power: 250 W RMS + 2 x 100 W RMS for two satellites
- Serves as a mobile 2.1 system together with MAXX-1206 2-way tops
- Balanced signal input XLR/6.3 mm jack L/R
- Additional stereo RCA input, with level switch
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor

Logistic

EAN / GTIN: 4026397729498
Weight: 37,40 kg
Length: 0.00 m
Width: 0.00 m
Height: 0.00 m
Bulky product

- Control via Bluetooth
- Rubber feet
- DSP presets: FLAT; DJ; LIVE
- Black metal grille with acoustic foam
- Application possibility: Standing
- Wheels optional
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

Package contents

- 1 x bass, 1 x power cord, 1 x strap, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Weight: 34,35 kg

OMNITRONIC MAXX-1206 2-Way Top 6.5" " 2x

Power:	Program: 200W Rated: 100W RMS
Frequency range:	100 - 17000 Hz
Sensitivity:	91 dB
Max. SPL:	115 dB
Dispersion angle:	90° x 60°
Impedance:	4 ohms
Attachment system:	Flange: Ø 35mm
Flying points:	3 x M8 thread
Connections:	Input: speaker via 1 x speaker built-in socket (F)
Speaker:	1 x woofer 6,5" Basket material: Steel Conematerial: Cardboard/paper 1 x compression tweeter highs 1"
Type of speaker:	Compact cabinet speaker
Carrying handle:	1 pc/pcs
Material:	MDF (Medium-density fiberboard), 16 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 20,4 cm Depth: 19 cm Height: 36,2 cm
Weight:	12,70 kg

OMNITRONIC MAXX-1206DSP 2.1 Active Subwoofer 12" "

Power supply:	230 V AC, 50 Hz
Power consumption:	500 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included

Device fuse:	5 x 20 mm, T 4 A Fuse replaceable
Power:	Rated: 250W RMS LF Rated: 2x 100W RMS HF
Frequency range:	38 - 250 Hz Bass 100 - 17000 Hz Top
Sensitivity:	97 dB
Max. SPL:	119 dB
DSP:	Digital signal processor
DSP presets:	FLAT; DJ; LIVE
Control:	Bluetooth
Bluetooth device name:	OMNITRONIC MAXX1206
Attachment system:	Flange: M20 thread
Circuitry:	Class D
Control elements:	Power switch, level control, Input sensitivity switch, connect, tone control
Controls:	Limiter
Status LED:	Power, signal, limit, pairing, DSP presets
Connections:	Input: line via 1 x stereo RCA Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 2 x 3-pin XLR Output: speaker via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via XLR or RCA or bluetooth, channel control via Rotary dial
Speaker:	1 x woofer 12" with ferrit magnet Basket material: Steel Conematerial: Cardboard/paper
USB port:	1 x Typ C, 2 A
Type of speaker:	Subwoofer
Type of construction:	Vented
Transport aid:	Rubber feet Wheels optional
Material:	MDF (Medium-density fiberboard), 16 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 38,4 cm Depth: 47,4 cm Height: 45,8 cm
Weight:	19,10 kg