

## OMNITRONIC MAXX-1810NG Active Subwoofer 18"

High-power 18" active subwoofer with DSP and Bluetooth, 800 W RMS

Art. No.: 11039081

GTIN: 4026397747300



**List price: 831.81 €**

incl. 19% VAT.

### Features:

- Multiband Compressor; Multistep Limiter; Active Phase Correction; Delay Compensation; 3-band EQ
- 4-channel mixer
- Stereo Bluetooth link for wireless stereo operation with 2 systems linked together

#### **bass**

- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- 4 x rubber feet
- Wheels optional

#### **integrated amplifier module**

- Digital signal processor
- DSP presets: MUSIC; LIVE; SPEECH; 80 Hz low cut; FLAT
- Control via Bluetooth
- Bluetooth: operating range up to 10m in buildings
- Multicolor LCD display
- The device is cooled by low-noise cooling fan

#### **Package contents**

- 1 x bass, 1 x power cord

### Logistic

EAN / GTIN: 4026397747300

Weight: 38,90 kg

Length: 0.66 m

Width: 0.57 m

Height: 0.66 m

Bulky product

### Technical specifications:

DSP:	Multiband Compressor; Multistep Limiter; Active Phase Correction; Delay Compensation; 3-band EQ
------	---

Bass	
Frequency range:	38 - 150 Hz
Max. SPL:	131 dB
Attachment system:	M20 thread
Speaker:	1 x woofer 18" with ferrit magnet Voice coil lows 3" Basket material: steel Conematerial: cardboard/paper
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet Wheels optional
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 51 cm Depth: 60 cm Height: 61,5 cm
Weight:	35,85 kg
Integrated amplifier module	
Power supply:	230 V AC, 50 Hz
Power consumption:	400 W
IP classification:	IP20
Protection class:	Protection class I
Output power:	500 W RMS (4 ohms) LF 2 x 150 W RMS (8 ohms) HF 1 x 300 W RMS (4 ohms) HF
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Device fuse:	5 x 20 mm, T 3,15 A fuse replaceable
DSP:	Digital signal processor
DSP presets:	MUSIC; LIVE; SPEECH; 80 Hz low cut; FLAT
Cooling:	1 x low-noise cooling fan
Filter:	Low cut: 80 Hz
Control:	Bluetooth
Bluetooth device name:	MAXX-1810NG
Range:	Bluetooth: range up to 10m in buildings
Carrier frequency:	2,4 GHz
Circuitry:	Class D
Display type:	Multicolor LCD display
Control elements:	Power switch, encoder, menu, BACK button
Controls:	Overheat; short-circuit; DC voltage; limiter
Status LED:	Limit
Connections:	Input: mic/line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)  Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)

Input: line via 1 x RCA (F) mounting version  
Output: line via 2 x 3-pin XLR (M) mounting version  
Output: speaker via 2 x speaker built-in socket (F)

Input channels:	3 x mono via XLR or jack, channel control via rotary dial 1 x stereo via RCA, channel control via rotary dial
Crossover frequency:	90 Hz
Power cord	
Cable construction:	3 x 0,75 mm <sup>2</sup> H05VV-F
Cable length:	1,8 m
Weight:	0,13 kg