

OMNITRONIC PAS-215PRO 2-Way Top

2-way speaker system for PA applications

Art. No.: 11039446

GTIN: 4026397438406



The article is no longer in our assortment.

Features:

- PA speaker system for medium-sized and large discotheques
- Rugged full-range top speaker qualified for suspended installation
- Rotatable constant directivity horn (asymmetrical) with coil-driver
- Passive 2-way crossover, PTC tweeter protection
- Bass-reflex system for powerful, dry bass
- Balanced frequency range with high sound-pressure
- Very high durability
- Optimized for combination with PAS subwoofers
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Trapezoidal wooden housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport
- The combination of several PAS speakers allows for large PA systems

Logistic

EAN / GTIN: 4026397438406

Weight: 23,00 kg

Length: 0.52 m

Width: 0.45 m

Height: 0.77 m

Technical specifications:

Power:	Program: 800W Rated: 400W RMS
Frequency range:	55 - 20000 Hz
Impedance:	8 ohms
Connections:	Input: speaker via 2 x speaker built-in socket (F)

Speaker:	1 x woofer 15"
Type of speaker:	Compact cabinet speaker
Dimensions:	Width: 43 cm Depth: 36,5 cm Height: 70 cm
Weight:	21,05 kg
Components:	38 cm woofer (15"), 2.5 cm horn (1")
Connection:	2 Speaker sockets
Sensitivity:	97 dB
Maximum SPL:	124 dB
Crossover frequency:	2 kHz
Dispersion angle:	50-100° x 55°