

OMNITRONIC PAS-151A PRO DSP Active Subwoofer

Active 15" PA bassreflex subwoofer, 500 W RMS

Art. No.: 11039630

GTIN: 4026397527452



Features:

- Active high-power bassreflex subwoofer for permanent installations and touring purposes
- Housing made of 18 mm plywood multilayered glued
- 1000 W Class D power amplifier with switch mode power supply
- 38 cm (15") bass speaker
- Balanced signal input XLR/6.3 mm jack L/R
- Parallel XLR line output L/R
- Adjustable crossover frequency 80-200 Hz
- DSP-controlled limiter
- Phase reversal switch
- M20 metal flange for mounting top speakers
- Incorporated carrying handles
- Scratch-resistant lacquer surface, steel grille and rubber feet
- Matching castors optionally available
- Digital signal processor
- Wheels optional

Logistic

EAN / GTIN: 4026397527452

Weight: 47,25 kg

Length: 0.78 m

Width: 0.56 m

Height: 0.70 m

Bulky product

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	670 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Power:	Rated: 500W RMS Program: 1000W
Frequency range:	45 - 120 Hz
Sensitivity:	96 dB
Max. SPL:	126 dB
DSP:	Digital signal processor
Circuitry:	Class D
Crossover frequency:	80-200 Hz
Speaker:	1 x woofer 15"
Type of speaker:	Subwoofer
Transport aid:	Wheels optional
Dimensions:	Width: 46 cm Depth: 68 cm Height: 59 cm
Weight:	42.60 kg
Woofer:	38 cm (15")
Signal input:	XLR L/R
Signal output:	XLR L/R
Acoustic loading:	Bassreflex
Amplifier:	Class D

Scope of delivery:
