

PSSO CSA-228B top, black

Compact speaker array for touring purposes and permanent installations

Art. No.: 11040800 GTIN: 4026397362701



The article is no longer in our assortment.

Description:

The CSA high-mid speaker units,

they are very powerful and feature a horn tweeter with 3.5 cm driver and, depending on the model, one or two 20 cm woofers (CSA-218 or CSA-228 respectively). The tweeter of the smaller version, the CSA-218, ensures a horizontal and vertical dispersion angle of 90° . Thus the CSA-218 can be used standing or lying without having to make compromises in terms of sound or directivity. The larger version, the CSA-228, is designed for upright use and has a dispersion angle of 90° x 40° .

Where should the CSA be used?

We can recommend mobile use. Concerts or weddings are supported in a powerful, resonant and linear way. But as it is quite versatile, the CSA should not be reduced to our suggestion only.

Features:

- Compact speaker array for touring purposes and permanent installations
- Speaker flange for mobile use included in the delivery
- Mounting bracket for permanent installation can be ordered separately
- Lightweight housing due to high-quality plastic
- Wide horizontal dispersion angle

Technical specifications:

Frequency range: 75 - 18000 Hz

Logistic

EAN / GTIN: 4026397362701

Weight: 17,10 kg Length: 0.76 m Width: 0.42 m Heigth: 0.40 m

| Dimensions: | Width: 66,5 cm |
|-------------------------|--|
| | Depth: 34 cm |
| | Height: 25 cm |
| Weight: | 14,45 kg |
| Rated power: | 300 W RMS |
| Program power: | 600 W |
| Components: | 2 x 20 cm mids speaker (2 x 8"), 3.4 cm driver $(1.33")$ |
| Connection: | 2 Speaker sockets (4-pin) |
| Sensitivity: | 95 dB |
| Maximum SPL: | 119 dB |
| Impedance: | 8 ohms |
| Crossover frequency: | 2.5 kHz |
| Dispersion angle: | H=90°, V=40° |
| Dimensions (H x W x D): | 250 x 665 x 340 mm |