

PSSO K-215DPX 2-Way Top 1000W

PRO PA speaker, 2 x 15" woofer, 1" horn, 100 W RMS, 4 ohms

Art. No.: 11041096

GTIN: 4026397516364

**The article is no longer in our assortment.****Features:**

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 20 mm birch plywood with steel corners
- Transport wheels
- 2 x 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter
- Horn exit 25 mm (1")
- Voice coil 50 mm (2")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Premium passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Applications: standing, on a subwoofer, suspended
- Trolley
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- European engineering

Logistic

EAN / GTIN: 4026397516364

Weight: 56,90 kg

Length: 0.55 m

Width: 0.53 m

Height: 1.26 m

Bulky product

Technical specifications:

Power:	Program: 2000W
	Rated: 1000W RMS
Frequency range:	44 - 19000 Hz

Sensitivity:	100 dB
Max. SPL:	136 dB
Dispersion angle:	70° x 50°
Impedance:	4 ohms
Connections:	Input: speaker via 2 x 2-pin SpeakON mounting version (F)
Crossover frequency:	1600 Hz
Speaker:	2 x woofer 15" 1 x horn 1"
Type of speaker:	Compact cabinet speaker
Transport aid:	Trolley
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Dimensions:	Width: 46,5 cm Depth: 47,8 cm Height: 1,17 m
Weight:	52,40 kg