

PSSO K-212 2-Way Top 300W

PRO PA speaker, 12" woofer, 1" horn, 300 W RMS, 8 ohms

Art. No.: 11041104

GTIN: 4026397481839



The article is no longer in our assortment.

Features:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 30 cm (12") bass speaker with diecast aluminum basket
- Rotatable 25 mm constant directivity horn tweeter (1", 44 mm voice coil)
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- European engineering

Package contents

- 1 x user manual, 1 x compact cabinet speaker

Logistic

EAN / GTIN: 4026397481839

Weight: 21,50 kg

Length: 0.40 m

Width: 0.43 m

Height: 0.68 m

Technical specifications:

Power:	Program: 600W Rated: 300W RMS
Frequency range:	55 - 19000 Hz
Sensitivity:	97 dB (1W/1m)

Max. SPL:	128 dB
Dispersion angle:	90° x 60°
Impedance:	8 ohms
Connections:	Input: speaker via 2 x 2-pin SpeakON mounting version (F)
Crossover frequency:	1900 Hz
Speaker:	1 x woofer 12" 1 x horn 1"
Type of speaker:	Compact cabinet speaker
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Dimensions:	Width: 34,7 cm Depth: 35,2 cm Height: 66 cm
Weight:	19,50 kg