

PSSO K-215SE 2-Way Top 600W

PRO PA speaker, 15" woofer, 1.5" horn, 600 W RMS, 8 ohms

Art. No.: 11041109

GTIN: 4026397545401



The article is no longer in our assortment.

Features:

- Rugged full-range top speaker, qualified for suspension and touring applications
 - Housing made of 15 mm/18 mm birch plywood
 - 38 cm (15") bass speaker with diecast aluminum basket
 - Rotatable constant directivity horn tweeter with titanium diaphragm
 - Horn exit 38 mm (1.5")
 - Voice coil 72 mm (2.8")
 - Premium custom-made drivers by European manufacturer CELTO Acoustique
 - Passive 2-way crossover
 - Bassreflex system
 - Parallel Neutrik Speakon connectors
 - Trapezoidal multi-functional housing with scratch-resistant lacquer surface
 - Impact-resistant steel grille with acoustic foam
 - Dual-angle-Flange for stand installation
 - Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
 - CELTO ACOUSTIQUE driver
 - Built with NEUTRIK connector
 - European engineering
- Package contents**
- 1 x top, 1 x user manual

Logistic

EAN / GTIN: 4026397545401

Weight: 32,45 kg

Length: 0.51 m

Width: 0.49 m

Height: 0.79 m

Bulky product

Technical specifications:

Power:

Program: 1200W

Rated: 600W RMS

Frequency range:	47 - 19000 Hz
Sensitivity:	99 dB (1W/1m)
Max. SPL:	127 dB
Dispersion angle:	80° x 50°
Impedance:	8 ohms
Connections:	Input: speaker via 2 x 2-pin SpeakON mounting version (F)
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 15" 1 x horn 1,35"
Type of speaker:	Compact cabinet speaker
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Dimensions:	Width: 44,5 cm Depth: 41,5 cm Height: 71 cm
Weight:	29,45 kg