

## PSSO K-215X 2-way top 600W

PRO PA speaker system

Art. No.: 11041110

GTIN: 4026397483048



### Features:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter
- Horn exit 35 mm (1.4")
- Voice coil 72 mm (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- CELTO ACOUSTIQUE driver

### Logistic

EAN / GTIN: 4026397483048

Weight: 35,00 kg

Length: 0.52 m

Width: 0.48 m

Height: 0.79 m

Bulky product

### Technical specifications:

Power:	Program: 1200W Rated: 600W RMS
Frequency range:	44 - 19000 Hz
Impedance:	8 ohms
Connections:	Input: speaker via 2 x speaker built-in socket (F)

Speaker:	1 x woofer 15"
Type of speaker:	Compact cabinet speaker
Use of brands:	CELTO ACOUSTIQUE driver
Dimensions:	Width: 71 cm Depth: 44.5 cm Height: 41.5 cm
Weight:	32.20 kg
Components:	38 cm woofer (15"), 3.6 cm horn (1.4")
Connection:	2 x Speakon
Sensitivity:	98 dB
Maximum SPL:	132 dB
Crossover frequency:	1.5 kHz
Dispersion angle:	80° x 50°
Dimensions (H x W x D):	710 x 445 x 415 mm

### **Scope of delivery:**

---