

CELTO ACOUSTIQUE iFIX6 G2 2-Way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043562

GTIN:



List price: on demand €

incl. 19% VAT.

Features:

- Real 120 W RMS with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- Audiophile grade crossover with right phase topology
- Warm and deep full range system
- HF compression driver with ketone polymere dome
- Birch multiplex cabinet with tongue and groove assembly
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with Mounting bracket
- For application areas such as: Theater; sports centres/gyms; Clubs/dancing school; restaurants, bars and hotels
- CELTO ACOUSTIQUE driver

Logistic

Package contents

- 1 x top, 1 x mounting bracket, 2 x knurled screw, 1 x nut, 2 x washer, 1 x safety eyelet, 1 x screw plug-in terminal

Technical specifications:

Power:	Rated: 120W AES Program: 240W Peak: 480W
Frequency range:	65 - 22000 Hz
Sensitivity:	90 dB (1W/1m)
Max. SPL:	117 dB

Dispersion angle:	85° x 85°
Impedance:	12 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Mounting bracket
Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive High-pass 2500 Hz, 12db/oct on LF Low-pass 2500 Hz, 18db/oct on HF Recommended High-pass 30 Hz, 24db/oct in full-range mode High-pass 60-140 Hz with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 6" with ferrit magnet Diaphragmmaterial: Ketone-Polymer Voice coil lows 1,5" 1 x compression tweeter highs 1" Voice coil compression tweeter highs 1"
Type of speaker:	Coaxial speaker; On-ceiling/on-wall speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 12 mm, CNC made with tongue and groove assembly
Color:	White, textured coating, painted
Dimensions:	Width: 19 cm Depth: 25 cm Height: 26 cm
Weight:	7,87 kg