

# CELTO ACOUSTIQUE iFIX10 G2 2-way Coaxial Speaker black

Big sound in small package, mounting bracket included

**Art. No.: 11043570** GTIN: 4026397746426











# List price: on demand €

incl. 19% VAT.

## Features:

- Real 300 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

# Package contents

 1 x top, 1 x mounting bracket, 1 x nut, 8 x washer, 1 x safety eyelet, 2 x screw, 1 x screw plug-in terminal

## Logistic

EAN / GTIN: 4026397746426

Weight: 14,80 kg Length: 0.37 m Width: 0.39 m Heigth: 0.42 m

#### **Technical specifications:**

Power:	Peak: 1200W	
	Program: 600W	
	Rated: 300W AES	
Frequency range:	95 - 22000 Hz	
Sensitivity:	97 dB (1W/1m)	
Max. SPL:	128 dB	

Dispersion angle:	80° conical
Impedance:	8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
	Mounting bracket
Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive 1500 Hz
	Recommended
	In subwoofer combination
	High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet
	Basket material: aluminum
	Voice coil lows 2,5"
	1 x annular compression driver 1"
	Voice coil annular 1,75"
	Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Closed Box
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	Black, textured coating, painted
Dimensions:	Width: 30 cm
	Depth: 30,4 cm
	Height: 30 cm
Weight:	12 kg