

## CELTO ACOUSTIQUE iFIX10 FR 2-Way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043574

GTIN:



**List price: on demand €**

incl. 19% VAT.

### Features:

- Real 250 W RMS with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- For application areas such as: Theater; sports centres/gyms; Clubs/dancing school; restaurants, bars and hotels
- With rigging points
- CELTO ACOUSTIQUE driver

#### Package contents

- 1 x top, 1 x mounting bracket, 1 x nut, 8 x washer, 1 x safety eyelet, 2 x screw, 1 x screw plug-in terminal

### Logistic

### Technical specifications:

Power:	Rated: 300W AES Program: 600W Peak: 1200W
Frequency range:	68 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	128 dB
Dispersion angle:	80° x 80°

Impedance:	8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Flying points:	5 x M8 thread
Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive 1500 Hz Recommended High-pass 30-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet Diaphragmmaterial: PEEK (H.T. polymer) Voice coil lows 2,5" 1 x Annular compression driver 1" Voice coil annular 1,75"
Type of speaker:	On-ceiling/on-wall speaker; Coaxial speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	White, textured coating, painted
Dimensions:	Width: 44,00 cm Depth: 29,80 cm Height: 31,60 cm
Weight:	17,05 kg