

CELTO iFIX10 FR 2-way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043574

GTIN:



List price: on demand €

incl. 19% VAT.

Features:

- Real 300 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- Warm and deep full range system
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

Technical specifications:

Power:	Peak: 1200W Program: 600W Rated: 300W AES
Frequency range:	68 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	128 dB
Dispersion angle:	80° conical
Impedance:	8 ohms

Attachment system:	Mounting bracket
Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive 1500 Hz Recommended In subwoofer combination High-pass 30-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet Basket material: aluminum Voice coil lows 2.5" 1 x annular compression driver 1" Voice coil annular 1.75" Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 15 mm, CNC made with tongue and groove assembly
Color:	White, textured coating, painted
Dimensions:	Width: 44.00 cm Depth: 29.80 cm Height: 31.60 cm
Weight:	14.5 kg

Scope of delivery:

1 x top
1 x mounting bracket
1 x nut
8 x washer
1 x safety eyelet
2 x screw
1 x screw plug-in terminal