

## CELTO iFIX10 FR 2-way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043574

GTIN:



### Features:

- Real 300 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- Warm and deep full range system
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

### Logistic

### Technical specifications:

|                   |   |
|-------------------|---|
| Power:            | Peak: 1200W<br>Program: 600W<br>Rated: 300W AES |
| Frequency range:  | 68 - 22000 Hz                                   |
| Sensitivity:      | 97 dB (1W/1m)                                   |
| Max. SPL:         | 128 dB  |
| Dispersion angle: | 80° conical                                     |
| Impedance:        | 8 ohms  |

|                       |   |
|-----------------------|---|
| Attachment system:    | Mounting bracket  |
| Connections:          | Input: speaker via screw plug-in terminal   |
| Crossover frequency:  | Passive 1500 Hz<br>Recommended<br>In subwoofer combination<br>High-pass 30-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer   |
| Speaker:              | 1 x woofer 10" with ferrit magnet<br>Basket material: aluminum<br>Voice coil lows 2.5"<br>1 x annular compression driver 1"<br>Voice coil annular 1.75"<br>Diaphragmmaterial: PEEK (H.T. polymer) |
| Type of speaker:      | On ceiling/on wall speaker; coaxial speaker   |
| Type of construction: | Vented  |
| Use of brands:        | CELTO ACOUSTIQUE driver   |
| Material:             | Birch multiplex, 15 mm, CNC made with tongue and groove assembly  |
| Color:                | White, textured coating, painted  |
| Dimensions:           | Width: 44.00 cm<br>Depth: 29.80 cm<br>Height: 31.60 cm  |
| Weight:               | 14.5 kg   |

### Scope of delivery:

1 x top  
1 x mounting bracket  
1 x nut  
8 x washer  
1 x safety eyelet  
2 x screw  
1 x screw plug-in terminal