

CELTO iFIX7 2-Way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043606

GTIN: 4026397662566



Features:

- Real 200 W RMS with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- Audiophile grade crossover with right phase topology
- Warm and deep full range system
- HF compression driver with ketone polymere dome
- Birch multiplex cabinet with tongue and groove assembly
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with mounting bracket
- Any RAL color available on request
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397662566

Weight: 12,00 kg

Length: 0.33 m

Width: 0.38 m

Height: 0.49 m

Technical specifications:

Power:	Program: 400W Rated: 200W RMS
Frequency range:	52 - 22000 Hz
Sensitivity:	92 dB (1W/1m)
Max. SPL:	121 dB
Dispersion angle:	80° x 80°
Impedance:	8 ohms

Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Mounting bracket
Connections:	Input: speaker via screw terminal
Crossover frequency:	Passive High-pass 2400 Hz, 12db/oct on LF Low-pass 2400 Hz, 18db/oct on HF Recommended High-pass 30 Hz, 24db/oct in full-range mode High-pass 60-140 Hz with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 7.5" with ferrit magnet Diaphragmmaterial: Ketone-Polymer Voice coil lows 2" 1 x compression tweeter highs 0.75" Voice coil compression tweeter highs 1"
Type of speaker:	Coaxial speaker; on ceiling/on wall speaker
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	White, textured coating, painted; any RAL color available on request
Dimensions:	Width: 37 cm Depth: 26.8 cm Height: 24.5 cm
Weight:	10.25 kg

Scope of delivery:

1 x top
1 x nut
2 x washer
1 x safety eyelet
1 x mounting bracket
2 x knurled screw