

## CELTO ACOUSTIQUE iFIX10 2-Way Coaxial Speaker black

Big sound in small package, mounting bracket included

Art. No.: 11043615

GTIN: 4026397662603



**List price: on demand €**

incl. 19% VAT.

### Features:

- Real 250 W RMS with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; Clubs/dancing school; restaurants, bars and hotels
- Any RAL color available on request

#### Package contents

- 1 x top, 1 x nut, 2 x washer, 1 x safety eyelet, 1 x mounting bracket, 2 x knurled screw

### Logistic

EAN / GTIN: 4026397662603

Weight: 13,80 kg

Length: 0.41 m

Width: 0.39 m

Height: 0.42 m

### Technical specifications:

Power:	Program: 500W Rated: 250W RMS
Frequency range:	90 - 18000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	127 dB
Dispersion angle:	75° x 75°
Impedance:	8 ohms

Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Connections:	Input: speaker via screw terminal
Crossover frequency:	Passive High-pass 1700 Hz, 12db/oct on LF Low-pass 1700 Hz, 18db/oct on HF Recommended In subwoofer combination Bi-amp mode only with external DSP processor High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet Diaphragmmaterial: Ketone-Polymer Voice coil lows 2,5" 1 x compression tweeter highs 1" Voice coil compression tweeter highs 1,75"
Type of speaker:	On-ceiling/on-wall speaker; Coaxial speaker
Type of construction:	Closed Box
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	Black, textured coating, painted; any RAL color available on request
Dimensions:	Width: 30 cm Depth: 30,5 cm Height: 30 cm
Weight:	11,80 kg