

CELTO iFIX10 2-Way Coaxial Speaker natural/white

Big sound in small package, mounting bracket included

Art. No.: 11043617

GTIN:



Features:

- Real 250 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- Birch multiplex cabinet with tongue and groove assembly
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with mounting bracket
- Any RAL color available on request
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

Technical specifications:

Power:	Program: 500W Rated: 250W RMS
Frequency range:	90 - 18000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	127 dB
Dispersion angle:	75° x 75°
Impedance:	8 ohms

Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Mounting bracket
Connections:	Input: speaker via screw terminal
Crossover frequency:	Passive High-pass 1700 Hz, 12db/oct on LF Low-pass 1700 Hz, 18db/oct on HF Recommended In subwoofer combination High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet Diaphragmmaterial: Ketone-Polymer Voice coil lows 2.5" 1 x compression tweeter highs 1" Voice coil compression tweeter highs 1.75"
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Closed Box
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	Nature, painted; any RAL color available on request
Dimensions:	Width: 30 cm Depth: 30.5 cm Height: 30 cm
Weight:	11.85 kg

Scope of delivery:

1 x top
1 x nut
2 x washer
1 x safety eyelet
1 x mounting bracket
2 x knurled screw