

CELTO iFIX10+ 2-Way Coaxial Speaker natural/white

Big sound in small package, mounting bracket included

Art. No.: 11043619

GTIN: 4026397688214



The article is no longer in our assortment.

Features:

- Real 300 W power handling with high-end sound quality
- HSP annular compression driver for unmatched spatial coherence
- Audiophile grade crossover with right phase topology
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- Birch multiplex cabinet with tongue and groove assembly
- Suitable for near-sound-field insonation with subwoofer (iFix13S or iFix17S) in fixed installations
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with mounting bracket
- Any RAL color available on request
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397688214

Technical specifications:

Power:	Program: 600W Rated: 300W AES
Frequency range:	95 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	128 dB
Dispersion angle:	90° x 90°

Impedance:	8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Mounting bracket
Connections:	Input: screw plug-in terminal
Crossover frequency:	Passive 1500 Hz on LF & HF Recommended High-pass 90-120 Hz with iFIX13S or iFIX17S subwoofer In subwoofer combination
Speaker:	1 x woofer 10" with ferrit magnet Basket material: steel Voice coil lows 2.5" Diaphragm material: PEEK (H.T. polymer) 1 x annular compression driver 1" Voice coil compression tweeter highs 1.7"
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Closed Box
Material:	Birch multiplex, CNC made with tongue and groove assembly
Color:	Nature, painted; any RAL color available on request
Dimensions:	Width: 30 cm Depth: 30.4 cm Height: 30 cm
Weight:	12.50 kg

Scope of delivery:

1 x top
1 x nut
6 x washer
1 x safety eyelet
1 x mounting bracket
2 x knurled screw
2 x screw