

CELTO ACOUSTIQUE HX118S Subwoofer

Exclusive design, ultimate exterior finish

Art. No.: 11043642

GTIN:



The article is no longer in our assortment.

Features:

- Real 1200 W RMS power capacity
- Premium 18" Neodymium driver with ± 11 mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- Titanium Finish metal parts
- 15-layer piano lacquer finish
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Any RAL color available on request
- For application areas such as: Theater; concerts/FoH's; Clubs/dancing school; restaurants, bars and hotels

Logistic

Technical specifications:

Power:	Program: 2400W Rated: 1200W RMS
Frequency range:	26 - 110 Hz
Sensitivity:	100 dB
Max. SPL:	134 dB
Dispersion angle:	Omnidirectional
Impedance:	8 ohms
Attachment system:	M20 thread

Connections:	Input: speaker via 2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Active mode only Recommended High-pass 30 Hz, 24db/oct Low-pass 80-110 Hz when used with HX12
Speaker:	1 x woofer 18" with neodymium magnet with dual demodulating rings Basket material: aluminum Voice coil woofer in/out wound 4"
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Material:	Birch multiplex, 25 mm, CNC made with tongue and groove assembly
Color:	Orange, high-gloss, 15-layer piano lacquer; any RAL color available on request
Dimensions:	Width: 58 cm Depth: 73 cm Height: 70 cm
Weight:	55,00 kg