


CELTO CT12 G3 2-way Fullrange Loudspeaker

Perfectly built speaker

Art. No.: 11043675

GTIN:



Features:

- Horn 90 degree rotatable for horizontal or vertical use
- Dual flange
- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Concerts/FoH's; clubs/dancing school; installation; mobile use; stage; theater; sports centres/gyms; multi-purpose hall

Logistic

Technical specifications:

Power:	Peak: 2400W Program: 1200W Rated: 600W AES
Frequency range:	50 - 22000 Hz
Sensitivity:	97 dB
Max. SPL:	131 dB
Dispersion angle:	80° x 50° rotatable horn
Impedance:	8 ohms
Attachment system:	Dual flange: Ø 35mm (0° / 10°)
Flying points:	17 x M8 thread

Control elements:	Mode switch (1+1- / 2+2-)
Connections:	2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Passive 1500 Hz
Speaker:	1 x woofer 12" Basket material: aluminum Voice coil lows 3" 1 x annular compression driver 1" Voice coil annular 1.75" Diaphragm material: PEEK (H.T. polymer)
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 35.6 cm Depth: 34.5 cm Height: 62.0 cm
Weight:	23.45 kg

Scope of delivery:

1 x top