

CELTO PM12 G3 2-way Fullrange Speaker

Perfectly built speaker

Art. No.: 11043683

GTIN:



List price: on demand €

incl. 19% VAT.

Features:

- Horn 90 degree rotatable for horizontal or vertical use
- Complies with DIN 18032-3 (Ball-proof)
- Dual flange
- With rigging points
- Built with NEUTRIK connector
- CELTO ACOUSTIQUE driver
- For application areas such as: Theater; music school; concerts/FoH's; restaurants, bars and hotels; sports centres/gyms; architecture; multi-purpose hall

Logistic

Technical specifications:

Power:	Peak: 2400W Program: 1200W Rated: 600W RMS
Frequency range:	40 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	131 dB
Dispersion angle:	80° x 50° rotatable horn
Impedance:	8 ohms
Standard:	DIN 18032-3 (Ball-proof),
Attachment system:	Dual flange: Ø 35mm (0° / 10°)

Flying points:	16 x M8 thread
Connections:	Speaker via 2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Passive 1500 Hz Recommended 40 Hz, 24db/oct in full-range mode 60-140 Hz with subwoofer
Speaker:	1 x woofer 12" with ferrit magnet Basket material: aluminum Voice coil woofer in/out wound 3" 1 x annular compression driver 1" with ferrit magnet Voice coil annular 1.75" Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	Compact cabinet speaker
Type of construction:	Transmission line
Use of brands:	Built with NEUTRIK connector CELTO ACOUSTIQUE driver
Material:	Birch multiplex, CNC made with tongue and grove assembly
Color:	Black, textured coating, painted
Dimensions:	Width: 34.8 cm Depth: 40.5 cm Height: 62.0 cm
Weight:	26.25 kg

Scope of delivery:

1 x compact cabinet speaker