

CELTO IR18S Subwoofer

IR18S: the right solution for a wide range of applications

Art. No.: 11043731

GTIN: 4026397680980



List price: on demand €

incl. 19% VAT.

Features:

- Real 1200 W RMS power capacity
- Premium 18" Neodymium driver with ± 11 mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- Fully integrated rigging for floor stacking and flying
- Wheels optional
- Wheelboard optional
- Rubberized Polyurea coating

Logistic

EAN / GTIN: 4026397680980

Technical specifications:

Power:	Peak: 4800W Program: 2400W Rated: 1200W RMS
Frequency range:	33 - 120 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	134 dB
Dispersion angle:	Omnidirectional
Impedance:	8 ohms
Attachment system:	1x M20 thread
Flying points:	With integrate rigging system

Control elements:	Mode switch (1+1- / 2+2-)
Connections:	3 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Active mode only Recommended Low-pass 70-120 Hz
Speaker:	1 x woofer 18" with neodymium magnet Basket material: aluminum Voice coil lows 4"
Type of speaker:	Subwoofer
Type of construction:	Vented
Transport aid:	Wheels optional Wheelboard optional
Material:	Birch multiplex, CNC made with tongue and groove assembly
Color:	Black, rubberized Polyurea coating
Dimensions:	Width: 42 cm Depth: 78 cm Height: 58.5 cm
Weight:	45.00 kg

Scope of delivery:

1 x bass