

CELTO ACOUSTIQUE T2.40 Amplifier

Class D touring amplifier with SMPS, 2 x 4000 W RMS (4 ohms), 2 x 2500 W RMS (8 ohms)

Art. No.: 11043805

GTIN: 4026397662764



List price: on demand €

incl. 19% VAT.

Features:

- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by cooling fan

Package contents

- 1 x amplifier, 4 x foot, 1 x power cord

Logistic

EAN / GTIN: 4026397662764

Weight: 18,10 kg

Length: 0.57 m

Width: 0.60 m

Height: 0.17 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Protection class:	Protection class I
Output power:	2 x 4000 W RMS (4 ohms) 2 x 2500 W RMS (8 ohms)
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	1,5 m detachable
Cooling:	2 x cooling fan , air flow from front to rear
Gain:	34 dB/ 2,82 V
Housing color:	Black
Circuitry:	Class D
Slew rate:	60 V/ μ s

Damping factor:	>800
Control elements:	Power switch, level control per channel
Status LED:	Power, signal, limit, protect, SOM
Connections:	Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR Output: speaker via 2 x 4-pol SpeakON mounting version (F)
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 46,8 cm Height: 8,8 cm
Weight:	15,60 kg