

CELTO C2.6 Amplifier

Class H core amplifier, 2 x 600 W RMS (4 ohms), 2 x 400 W RMS (8 ohms)

Art. No.: 11043807

GTIN: 4026397743234



Features:

- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan

Logistic

EAN / GTIN: 4026397743234

Weight: 16,45 kg

Length: 0.53 m

Width: 0.57 m

Height: 0.17 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Protection class:	Protection class I
Output power:	2 x 600 W RMS (4 ohms) 2 x 400 W RMS (8 ohms) 1 x 1200 W RMS bridged (8 ohms)
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	8 A fuse resettable
Frequency range:	20 - 20000 Hz
S/N ratio:	>110 dB
THD:	<0.1 % at 1 kHz
Cooling:	1 x temperature-controlled fan , air flow from front to rear
Impedance:	Input: 20 kOhm

Gain:	37.3 dB
Circuitry:	Class H
Slew rate:	>15 V/ μ s
Damping factor:	>500
Crosstalk:	>65 dB
Control elements:	Power switch, level control per channel, mode switch (stereo/parallel/bridged), groundlift selector
Controls:	Softstart; short-circuit; Overvoltage; overload; current limiting; DC voltage; overheat
Status LED:	Power, signal, limit, protect
Connections:	Input: line via 2 x 3-pin XLR (F) mounting version Output: line via 2 x 3-pin XLR (M) mounting version Output: speaker via 2 x 4-pol SpeakON mounting version (F) Output: 4 x screw plug-in terminal
Input sensitivity:	0.775 V
Color:	Black, matte, painted
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48.3 cm Depth: 38.8 cm Height: 8.8 cm
Weight:	14.45 kg

Scope of delivery:

1 x amplifier
1 x power cord
4 x foot