

CELTO ACOUSTIQUE SP26 Digital Speaker Controller

Art. No.: 11043813

GTIN: 4026397688207



List price: on demand €

incl. 19% VAT.

Features:

- Digital signal processor
- Sample rate: 96 kHz
- (19") 48.3 cm rack installation
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x controller, 1 x power cord, 1 x uSB cable, 1 x network cable, 4 x foot, 1 x cD

Logistic

EAN / GTIN: 4026397688207

Weight: 3,10 kg

Length: 0.55 m

Width: 0.30 m

Heigh: 0.10 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 35 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz
THD:	<0,003 % at 1 kHz
Network connection:	Protocol: Ethernet TCP/IP via
DSP:	Digital signal processor
Impedance:	Input: 40 kOhm Output: 60 Ohm
Gain:	Input: -40 dB to +6 dB

	Output: -40 dB to +15 dB
Filter:	Linkwitz-Riley; Butterworth; Bessel; 12db/oct; 18db/oct; 24db/oct; 48db/Okt
Delay:	0 - 1000 ms
Dynamic range:	Input: 112 dB Output: 118 dB
Sample rate:	96 kHz
Connections:	Input: line via 2 x 3-pin XLR Output: line via 6 x 3-pin XLR
Crossover frequency:	20-20000 Hz
Max. level:	Input: +18 dBu Output: +20 dBu
USB port:	Typ B
Housing design:	(19") 48.3 cm rack installation
Dimensions:	Width: 48,3 cm Depth: 20 cm Height: 4,4 cm
Weight:	2,72 kg