

## INTUSONIC HPA41 4-zone Paging Station

4-zone paging station with customizable auto chime player

Art. No.: 12604192

GTIN: 4026397758139



**List price: 260.61 €**

incl. 19% VAT.

### Description:

The INTUGRID HPA41 is part of the modular and flexible family of INTUGRID system components and serves as a paging station for systems up to 4 zones. Unique in its approach, it contains an on-board chime player. Once this is activated, the chime will play first once the paging is invoked, thus saving the operator from the discomfort of triggering the chime separately.

To customize the experience, the factory chime sound can be overwritten via the IntuLink bus or changed by swapping the memory IC. For further convenience of less experienced users, a microphone level indicator shows whether the distance to the microphone is correct.

Zones can either be paged all at once or via a preselection, which can be cleared by the touch of a button. Chime and microphone volumes are adjustable by separate rear-panel controls, and the professional-grade external symmetrical power supply (SPA12) allows high-headroom audio.

### Features:

- 4 zone selective paging
- All zone paging
- Auto-chime player with exchangeable chime sounds
- Electret gooseneck microphone
- Desktop console housing
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397758139

Weight: 1,20 kg

Length: 0.34 m

Width: 0.21 m

Height: 0.10 m

## Technical specifications:

---

Type:	Gooseneck microphone
Power supply:	100-240 V AC, 50/60 Hz 15V DC 500 mA
Power consumption:	5 W
IP classification:	IP20
Power connection:	Mains input via Mini XLR (F) 3-pin power supply cord with Euro plug included
Capsule type:	Electret Size: Ø 13 mm x 60 mm
Network connection:	2x RJ-45 (F) mounting version
Phantom power:	15 V DC
Housing color:	Black matte; anthracite matte
Zone output:	4 switchable zones
Control elements:	Power switch, level control, chime button, clear button
Status LED:	Speech-Level
Connections:	Input: RS 485 via 1 x RJ-45 (F) mounting version Output: RS 485 via 1 x RJ-45 (F) mounting version
Channels:	Microphone channel: 1 x mono via XLR, channel control via rotary dial
Housing design:	Desktop console housing
Weight:	0.90 kg
Dimensions:	Width: 20.5 cm Depth: 15.5 cm Height: 6 cm
Dimensions:	Length: 28 cm Diameter: Ø 2.7 cm

## Scope of delivery:

---

- 1 x device
- 1 x microphone
- 1 x windshield
- 1 x external mains adapter
- 1 x power cord
- 1 x user manual