

RELACART UD-200 UHF-Gooseneck Microphone

UHF gooseneck microphone with PLL multifrequency transmitter

Art. No.: 13055222

GTIN: 4026397525823



The article is no longer in our assortment.

Features:

- Gooseneck microphone with UHF pilot tone technology (PLL)
- 2 license-free frequency ranges: 823-832 MHz (Duplex Gap) and 863-865 MHz
- Parallel operation of up to 9 transmitters is possible without any interference
- Suitable for the WAM-400 automatic mixer
- Infrared interface for easy and error-free synchronization with the receiver via infrared signal
- LCD for battery status, frequency and channel
- Mute function
- Durable metal diecast housing
- Operation via 2 x 1.5 V batteries (type AA), not included
- License-free and approved in large parts of the EU (please check Duplex Gap on a country-by-country basis)
- Polar pattern: Cardioid
- Operating range up to 60m with line-of-sight
- UHF 863 - 865 MHz License-free and approved in Europe
- UHF 823 - 832 MHz License-free and approved in large parts of Europe

Package contents

- 1 x microphone, 1 x declaration of conformity, 1 x battery

Logistic

EAN / GTIN: 4026397525823

Weight: 1,25 kg

Length: 0.12 m

Width: 0.14 m

Height: 0.45 m

Technical specifications:

Type: Gooseneck microphone

Power supply: 3 V DC

Power connection: Battery/battery pack

Capsule type:	Electret
Polar pattern:	Cardioid
Battery:	2 x 1.5 V AA Mignon R06 zinc carbon included
Frequency range:	50 - 17000 Hz
Range:	Range up to 60m with line-of-sight
Frequency band:	UHF 863 - 865 MHz; UHF 823 - 832 MHz
Switching bandwidth:	11 MHz
Frequency stability:	± 0,0005 %
RF power output:	10 mW
Modulation:	FM
Frequency selection:	Switchable frequencies
Switch:	On/off switch
Material:	Metal
Color:	Black
Dimensions:	Width: 11,5 cm Depth: 14 cm Height: 45,5 cm
Weight:	880 g