

## OMNITRONIC DR-415 Wireless receiver

Multifrequency wireless receiver, diversity system

Art. No.: 13061100

GTIN: 4026397114003



**The article is no longer in our assortment.**

### Features:

- 16 UHF frequencies (800.100 - 813.000 MHz) selectable via DIP switches
- Diversity system with two antennas
- Operation in the low-interference UHF band
- LED display for power supply and signal input
- Squelch control to eliminate noise bursts
- Output level control
- 6.3 mm and XLR output
- Operation via supplied power unit
- A wireless microphone or a belt transmitter with lavalier microphone or headset microphone can be ordered separately
- License-free and approved in Germany

### Logistic

EAN / GTIN: 4026397114003

Weight: 1,30 kg

Length: 0.33 m

Width: 0.35 m

Height: 0.07 m

### Technical specifications:

Power consumption:	140,00 W
Dimensions:	Width: 21 cm Depth: 16,5 cm Height: 4,4 cm
System:	Switching Diversity, one channel

Carrier frequency:	UHF 800.100-813.000 MHz (16 ch.) 800.875, 801.375, 802.375, 803.125, 803.875, 804.500, 805.125, 805.875, 806.625, 807.375, 807.875, 808.375, 809.125, 810.250, 810.875, 811.875 MHz
Frequency stability:	±0,005 %
T.H.D.:	<1 % at 1 kHz
Tone signal:	32.768 kHz
S/N-ratio:	>94 dB at 48 kHz deviation and 60 dB antenna input
Input sensitivity:	8 dB
Selectivity:	>50 dB
Dynamic range:	>96 dB
Modulation method:	FM-frequency modulation
Coverage:	>80 m (with line-of-sight)
AF response:	50-15000 Hz (±3 dB)
Audio output:	Mono 6.3 mm jack socket or balanced XLR
Dimensions:	210 x 165 x 44 mm
Weight:	0.55 kg