

OMNITRONIC SR-315 Wireless receiver

Multifrequency wireless receiver

Art. No.: 13061500

GTIN: 4026397114027



Features:

- 16 UHF frequencies (800.100 - 813.000 MHz) selectable via DIP switches
- Telescope antenna
- LED display for power supply and signal input
- Squelch control to eliminate noise bursts
- Output level control
- 6.3 mm and XLR output
- Operation via supplied power unit
- A wireless microphone or a belt transmitter with lavalier microphone or headset microphone can be ordered separately
- License-free and approved in Germany

Logistic

EAN / GTIN: 4026397114027

Weight: 1,40 kg

Length: 0.35 m

Width: 0.31 m

Height: 0.07 m

Technical specifications:

Power consumption:	130.00 W
Frequency band:	UHF
Dimensions:	Width: 21 cm Depth: 16.5 cm Height: 4.4 cm
System:	Non-diversity, one channel
Carrier frequency:	UHF 800.100-813.000 MHz (16 ch.)

800.875, 801.375, 802.375, 803.125, 803.875,
804.500, 805.125, 805.875, 806.625, 807.375,
807.875, 808.375, 809.125, 810.250, 810.875,
811.875 MHz

Frequency stability:	±0.005 %
T.H.D.:	<1 % at 1 kHz
Tone signal:	32.768 kHz
S/N-ratio:	>94 dB at 48 kHz deviation
Input sensitivity:	8 dB
Selectivity:	>50 dB
Dynamic range:	>96 dB
Modulation method:	FM-frequency modulation
Coverage:	>30 m (with line-of-sight)
Frequency range:	50-15000 Hz (±3 dB)
Audio output:	Mono 6.3 mm jack socket or balanced XLR
Dimensions (LxHxH):	210 x 165 x 44 mm
Weight:	0.5 kg

Scope of delivery:
