

## PSSO WISE TWO 2-Channel True Diversity Receiver 518-548MHz

License-free true diversity wireless receiver with 2.4GHz iSync control management

Art. No.: 13063391

GTIN: 4026397683097



**List price: 653.31 €**

incl. 19% VAT.

### Features:

- Professional multifrequency wireless receiver with true diversity reception for stage use
  - High-grade components and intelligent features ensure best performance and high reliability
  - Ideal for large multi-channel systems (parallel operation possible up to 26 systems)
  - 100 preset channels in 10 channel groups
  - 2.4 GHz iSync - real-time synchronization and monitoring
  - Automatic frequency setup
  - Pilot frequency squelch technology delete wireless RF interference
  - Multifunctional jogdial for menu settings
  - Lock function for prevents undesired changes to settings
  - Mic/line selector switch
  - 2 detachable BNC antennas allow for use with external antenna divider
  - 2 receivers can share a single power adapter
  - Multicolor LCD display
  - UHF 518 - 548 MHz License-free and approved in large parts of Europe
  - Operating range up to 60m with line-of-sight
  - (19") 48.3 cm rack installation 1 U
  - Firmware can be updated
- Package contents**
- 1 x receiver, 1 x external mains adapter, 1 x power cord, 3 x antenna, 2 x bnc cable, 1 x jack cable, 1 x adapter cable, 4 x foot, 2 x holder, 2 x windshield, 1 x user manual, 1 x declaration of conformity, 4 x battery

### Logistic

EAN / GTIN: 4026397683097

Weight: 3,72 kg

Length: 0.53 m

Width: 0.32 m

Height: 0.13 m

## Technical specifications:

Type:	Receiver
Power supply:	100-240 V AC, 50/60 Hz 12-15 V DC 1,5 A
Power consumption:	8 W
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Number of channels:	2
Frequency range:	50 - 20000 Hz
S/N ratio:	>96 dB
THD:	<0,1 % at 1 kHz
Gain:	Microphone -32 dB to +4 dB Output: -32 dB to +4 dB
Range:	Range up to 60m with line-of-sight
Frequency band:	UHF 518 - 548 MHz
Diversity:	True diversity
Modulation:	FM
Frequency selection:	100 Switchable frequencies In 10 groups Frequencies automatically scannable
Display type:	Multicolor LCD display
Control elements:	Power switch, groundlift selector, menu, encoder
Connections:	Antenna via 2 x BNC (F) 12-15 V Antenna via 1 x SMA (F) mounting version Output: mic/line via 2 x 3-pin XLR Output: mic/line via 2 x 6.3 mm jack socket (mono) mounting version Output: for audio/data link via 2 x BNC (F)
Channels:	Microphon chanal: 2 x mono with Mic-line switch via XLR or jack
Switch:	Low cut switch
Material:	Metal
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48 cm Depth: 27 cm Height: 4,3 cm
Weight:	2,9 kg