

OMNITRONIC FAS TWO 2-Channel Wireless Receiver 660-690MHz

License-free miniature wireless microphone system, digital modulation, high ease of use

Art. No.: 13063450

GTIN: 4026397718560



List price: 57 €

incl. 19% VAT.

Description:

The FAS TWO is a reliable miniature 2-channel wireless microphone system with high ease of use for live stage performances, weddings, karaoke, street performers or band rehearsals. The units are ready to use on the spot without lengthy setup and feature lithium-ion batteries with an operating time of up to 5 hours.

Features:

- 2 frequency banks with 20 adjustable frequencies each available
- Quick pairing at the touch of a button
- Receiver automatically adopts frequency setting
- Ultra-low latency
- Digital transmission provides for high resistance to interference and unique sound quality
- Small lightweight version
- Multiple receivers can be combined with 2 transmitters as desired
- Battery operation up to 5h
- Operating range up to 30m with line-of-sight
- Sample rate: 48 kHz
- Cordless, flexible and versatile
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels; small rental; product presentations and lectures

Package contents

- 1 x receiver, 1 x adapter, 1 x external mains adapter, 1 x uSB cable, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397718560

Weight: 0,21 kg

Length: 0.30 m

Width: 0.09 m

Height: 0.04 m

Technical specifications:

Type:	Receiver
Power supply:	5 V DC 1 A
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter included Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3,7 V, 800 mAh, 3,96 Wh
Battery pack:	Battery operation up to 5h
Number of channels:	2
Frequency range:	60 - 15000 Hz
S/N ratio:	>92 dB
THD:	<0,8 % at 1 kHz
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 660 - 690 MHz
Modulation:	Pi/4 DQPSK
Frequency selection:	40 In 2 groups Frequencies automatically scannable Switchable frequencies
Sample rate:	48 kHz
Status LED:	Power, chanal source
Connections:	Output: mic/line via 1 x 3.5 mm jack (mono)
Max. level:	Output: mic/line -1,90 dBu, unbal.
Material:	Metal
Color:	Black
Weight:	140 g
Receiver	
Dimensions:	Length: 17 cm Width: 3,6 cm Height: 2,2 cm
Weight:	50 g