

OMNITRONIC AIRSIS 2.4G Wireless XLR Kit (mic/line)

Wireless XLR audio system for dynamic microphones and line signals, 2.4 GHz

Art. No.: 13072203

GTIN: 4026397744729



List price: 117.81 €

incl. 19% VAT.

Features:

- Plug-on system with transmitter and receiver ready to use
 - Eliminates troublesome cable runs
 - For use with mixers, active speakers and dynamic microphones
 - Automatic pairing
 - 24 bit/48 kHz for the ultimate sound quality
 - Rechargeable lithium batteries
 - Several receivers can be coupled with a single transmitter
 - LED indicator for monitoring the operating status
 - Sample rate: 48 kHz
 - Note: The device does not provide phantom power. Therefore, only dynamic microphones and condenser microphones that are battery-operated can be used.
 - Operating range up to 30m with line-of-sight
 - 2.4 GHz license-free worldwide
 - Ultra-low latency
- transmitter**
- Cordless, flexible and versatile
- receiver**
- Cordless, flexible and versatile
- Package contents**
- 1 x transmitter, 1 x receiver, 1 x USB cable, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397744729

Weight: 0,24 kg

Length: 0.15 m

Width: 0.14 m

Height: 0.04 m

Technical specifications:

Type: Audio transmission

Protection class:	Protection class III
Power connection:	Mains input via USB C (W) mounting version power supply cord for USB A mains connection (provided)
Frequency range:	20 - 20000 Hz
THD:	Mic/line <0,02 % at 1 kHz
Range:	Range up to 30m with line-of-sight
Frequency band:	2.4 GHz
Latency:	5,8 ms
Housing color:	Black matte
Sample rate:	48 kHz
Converter:	24 bit
Material:	Plastic
Weight:	0,14 kg
Transmitter	
Power connection:	Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3,7 V, 600 mAh, 2,22 Wh
Control elements:	Power switch, Input sensitivity switch
Status LED:	Power, Mute, charge status indicator, pairing
Connections:	Input: mic/line via 1 x 3-pin XLR (F) mounting version
Input channels:	1 x mono with mic-line switch
USB port:	1 x type C
Dimensions:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm
Weight:	0,047 kg
Receiver	
Power connection:	Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3,7 V, 800 mAh, 2,96 Wh
Control elements:	Power switch
Status LED:	Power, Mute, charge status indicator, pairing
Connections:	Output: mic/line via 1 x 3-pin XLR (M) mounting version
USB port:	1 x type C
Dimensions:	Length: 10,7 cm Width: 3,0 cm Depth: 2,2 cm
Weight:	0,044 kg
USB cable	
Cable length:	0,5 m
Plug A:	1 x USB A (M)
Plug B:	2 x USB C (M)
Weight:	0,02 kg