



The article is no longer in our assortment.

Features:

FUTURELIGHT PLB-230 Moving Head

High performance beam with Osram Sirius HRI 230 W lamp and LED ring with RGB color mixture

- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Number of scenes in Program Run can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With already installed Osram Sirius HRI 230 W lamp
- 12 powerful LEDs 3 W 3in1 TCL RGB
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; Focus motor-driven
- Gobo effect
- Color wheel with 14 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 8 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement

Logistic

- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- With a beam angle of 1,3°

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Trunk case with castors, PRO version

- For optimal security
- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

High-quality safety rope

- For securing loads over people
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x rope, 1 x connector

Technical specifications:

FUTURELIGHT PLB-230 Moving Head

| | |
|---------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 325,00 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug |
| Lamp type: | Discharge lamp |
| LED: | 12 x 3 W 3in1 TCL RGB |
| Max. TILT movement: | 270° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Max. PAN movement: | 540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Gobo wheel with rotating gobos; Focus motor-driven |
| Color generation: | Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with rotating gobos, 8 gobos and open Outside diameter 14mm |

Image diameter 6mm
Shake effect
Gobos changeable
Slot-in gobo system for easy gobo replacement

| | |
|------------------------|--|
| DMX channels: | 17; 19; 21; 24 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX; stand-alone; W-DMX by wireless solution; Sound to light via Microphone |
| Preprogrammed in: | LED PC-Control 512; Light Captain; Light´J |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 1,3° |
| Beam angle (1/2 peak): | 1,3° |
| Housing color: | Black |
| Dimensions: | Width: 25 cm Depth: 42,4 cm Height: 34,3 cm |
| Weight: | 16,20 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

| | |
|--------------------------|---|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 8 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 29,5 cm x 27 cm x 41 cm |
| Middle compartment: | 9,5 cm x 54 cm x 46,5 cm |
| Inside dimensions: | 94,5 cm x 56 cm x 46,5 cm |
| Dimensions: | Width: 1,025 m Depth: 60,5 cm Height: 72 cm |
| Weight: | 41,90 kg |

EUROLITE TPC-10 Coupler, silver

| | |
|-------------------------------|-------|
| Maximum load BGV C1 (8-fold): | 75 kg |
|-------------------------------|-------|

| | |
|-------------------------|---|
| Max. load WLL (4-fold): | 150 kg |
| Tube diameter sector: | 48 - 50 mm |
| Material: | Aluminum |
| Color: | Silver |
| Mounting screw: | M10 |
| Dimensions: | Length: 10 cm Width: 3 cm Depth: 9 cm |
| Weight: | 160 g |

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

| | |
|-----------------------------------|---|
| Secured weight (BGV C1): | Max. 15 kg |
| Design of the core: | 6 x 19 FC |
| Strength classification: | 1770 |
| Standard: | DIN EN 12385-4:2008-06, DIN 56927:2009-03 |
| Nominal tensile strenght of rope: | 1770 N/mm ² |
| Wire surface: | Zinc-plated |
| Color: | Silver |
| Temperature range: | -40° C - +100° C |
| Dimensions: | Length: 1 m Diameter: Ø 4 mm |
| Weight: | 100 g |
| Length weigth: | 0,0554 kg/m |