



The article is no longer in our assortment.

Features:

FUTURELIGHT DMB-150 LED Moving Head

LED beam with 150 W COB LED

- Extremely high light output
- Very narrow illumination angle of 5°
- Light beam can easily be centered and moved exactly
- 10, 12, 13 or 16 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and beam shaper
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 11 static gobos plus open
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually

Logistic

- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- 1 powerful LED
- Gobos
- Beam effect
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; Sound to light via Microphone; RDM
- Preprogrammed in LED PC-Control 512; Light Captain

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Trunk case with castors, PRO version

- For optimal security
- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

High-quality safety rope

- For securing loads over people
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x rope, 1 x connector

Technical specifications:

FUTURELIGHT DMB-150 LED Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	195 W
IP classification:	IP20
Lamp type:	LED lamp
LED:	1
Max. TILT movement:	270° Positioning
Max. PAN movement:	630° Positioning
Equipment:	Gobos
DMX channels:	10
Cooling:	Temperature-controlled fan
Control:	DMX; stand-alone; Sound to light via Microphone; RDM
Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle (1/2 peak):	5°

Housing color:	Black
Dimensions:	Width: 34,3 cm Depth: 24 cm Height: 42,8 cm
Weight:	12,05 kg
DMX channels:	10/12/13/16
DMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED type:	Array 150 W
LED number:	1
Beam angle:	5°
Color-wheel:	8 dichroic filters plus open
Static gobo-wheel:	11 gobos and open
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	343 x 250 x 428 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	29,5 cm x 27 cm x 41 cm
Middle compartment:	9,5 cm x 54 cm x 46,5 cm
Inside dimensions:	94,5 cm x 56 cm x 46,5 cm
Dimensions:	Width: 1,025 m Depth: 60,5 cm Height: 72 cm
Weight:	41,90 kg

EUROLITE TPC-10 Coupler, silver

Maximum load BGV C1 (8-fold):	75 kg
Max. load WLL (4-fold):	150 kg
Tube diameter sector:	48 - 50 mm
Material:	Aluminum
Color:	Silver

Mounting screw:	M10
Dimensions:	Length: 10 cm Width: 3 cm Depth: 9 cm
Weight:	160 g

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

Secured weight (BGV C1):	Max. 15 kg
Design of the core:	6 x 19 FC
Strength classification:	1770
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 1 m Diameter: Ø 4 mm
Weight:	100 g
Length weigth:	0,0554 kg/m