



**The article is no longer in our assortment.**

### Features:

#### FUTURELIGHT DMH-60 LED Moving Head

High performance LED Moving Head with 60 W LED

- 1 extra bright 60 W LED for best luminance
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 3D prism and frost filter
- Macro function for rotating gobos/rotating prism combinations
- Color wheel with 8 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Power standby mode
- Automatic position correction
- PAN angle switchable between 630° and 540°
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Sound-controlled via built-in microphone
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset

### Logistic

- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- DMX control via every standard DMX controller
- Control via Sound to light via Microphone; DMX; RDM
- Preprogrammed in Light J

#### **ROADINGER Flightcase 2x DMH-30/DMH-40**

PRO flightcase for 2 x FUTURELIGHT DMH-60/DMH-40/DMH-30 LED moving-head

- Developed for 51841836 FUTURELIGHT DMH-60 LED Moving Head, 51841835 FUTURELIGHT DMH-40 LED Moving Head, 51841825 FUTURELIGHT DMH-30 LED Moving Head or comparable Moving Heads
- Suitable for 2 units
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 high-quality butterfly locks
- 2 high-quality plated case handles
- For perfect protection
- Castors
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### **EUROLITE Safety Bond AG-15 4x1000mm up to 15kg**

High-quality safety rope

- For securing loads over people
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

##### **Package contents**

- 1 x rope, 1 x connector

#### **Technical specifications:**

---

##### **FUTURELIGHT DMH-60 LED Moving Head**

|                        |  |
|------------------------|--|
| Power supply:          | 100-240 V AC, 50/60 Hz                       |
| Power consumption:     | 245 W  |
| Max. TILT movement:    | 270° Positioning                             |
| Max. PAN movement:     | 630° Positioning                             |
| Flash rate:            | 1 - 13 Hz                                    |
| Gobos:                 | Outside diameter 27mm<br>Image diameter 22mm |
| DMX channels:          | 14   |
| Control:               | Sound to light via Microphone; DMX; RDM      |
| Preprogrammed in:      | Light J                                      |
| Beam angle (1/2 peak): | 14°  |
| Color:                 | Black  |

|                                |   |
|--------------------------------|---|
| Dimensions:                    | Width: 30,1 cm<br>Depth: 24,7 cm<br>Height: 40,6 cm |
| Weight:                        | 11,40 kg  |
| DMX channels:                  | 14  |
| DMX connection:                | 5-pin and 3-pin XLR                                 |
| Sound-control:                 | via built-in microphone                             |
| Wireless signal transmission:  | 2.4 GHz (ISM)                                       |
| Flash-rate:                    | 13 Hz   |
| LED type:                      | 60 W, white   |
| LED number:                    | 1   |
| Beam angle:                    | 14°   |
| Color-wheel:                   | 8 dichroic filters plus open                        |
| Rotating gobo-wheel:           | 7 gobos and open                                    |
| Outside diameter of the gobos: | 27 mm   |
| Image diameter of the gobos:   | 22 mm   |
| Maximum PAN-movement:          | 630°  |
| Maximum TILT-movement:         | 270°  |
| Dimensions (L x W x H):        | 301 x 247 x 406 mm                                  |
| Legal specifications           |   |
| Special product:               | Not designed for household room illumination        |
| Intended use:                  | Show effect lighting                                |

#### **ROADINGER Flightcase 2x DMH-30/DMH-40**

|                                 |   |
|---------------------------------|---|
| Maximum load:                   | 50 kg   |
| Transport aid:                  | Castors   |
| Material:                       | Birch multiplex, 7 mm                           |
| Color:                          | Dark brown, laminated                           |
| Dimensions:                     | Width: 72,5 cm<br>Depth: 40 cm<br>Height: 68 cm |
| Weight:                         | 18,80 kg  |
| Strength:                       | 7 mm  |
| Outside dimensions (W x D x H): | 725 x 400 x 680 mm                              |
| Inside dimensions (W x D x H):  | 685 x 360 x 460 mm                              |

#### **EUROLITE TPC-10 Coupler, silver**

|                               |            |
|-------------------------------|------------|
| Maximum load BGV C1 (8-fold): | 75 kg      |
| Max. load WLL (4-fold):       | 150 kg     |
| Tube diameter sector:         | 48 - 50 mm |
| Material:                     | Aluminum   |
| Color:                        | Silver     |
| Mounting screw:               | M10        |

|             |   |
|-------------|---|
| Dimensions: | Length: 10 cm<br>Width: 3 cm<br>Depth: 9 cm |
| Weight:     | 160 g                                       |

**EUROLITE Safety Bond AG-15 4x1000mm up to 15kg**

|                                   |   |
|-----------------------------------|---|
| Secured weight (BGV C1):          | Max. 15 kg                                |
| Design of the core:               | 6 x 19 FC                                 |
| Strength classification:          | 1770                                      |
| Standard:                         | DIN EN 12385-4:2008-06, DIN 56927:2009-03 |
| Nominal tensile strength of rope: | 1770 N/mm <sup>2</sup>                    |
| Wire surface:                     | Zinc-plated                               |
| Color:                            | Silver                                    |
| Temperature range:                | -40° C - +100° C                          |
| Dimensions:                       | Length: 1 m<br>Diameter: Ø 4 mm           |
| Weight:                           | 100 g                                     |
| Length weight:                    | 0,0554 kg/m                               |