



Features:

FUTURELIGHT DMH-60 LED Moving Head

High performance LED moving head with 60 W LED

- 1 extra bright 60 W LED for best luminance
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 3D prism and frost filter
- Macro function for rotating gobos/rotating prism combinations
- Color wheel with 8 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Power standby mode
- Automatic position correction
- PAN angle switchable between 630° and 540°
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Sound-controlled via built-in microphone
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset

Logistic

- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- DMX control via every standard DMX controller
- Control via sound to light via microphone; DMX; RDM

ROADINGER Flightcase 2x DMH-30/DMH-40

PRO flightcase for 2 x FUTURELIGHT DMH-60/DMH-40/DMH-30 LED moving head

- Developed for 51841836 FUTURELIGHT DMH-60 LED Moving Head, 51841835 FUTURELIGHT DMH-40 LED Moving Head, 51841825 FUTURELIGHT DMH-30 LED Moving Head or comparable Moving Heads
- Suitable for 2 units
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 high-quality butterfly locks
- 2 high-quality plated case handles
- For perfect protection
- Castors
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

High-quality safety rope

- For securing loads over people
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT DMH-60 LED Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	245 W
Max. TILT movement:	270° positioning
Max. PAN movement:	630° positioning
Flash rate:	1 - 13 Hz
Gobos:	Outside diameter 27mm Image diameter 22mm
DMX channels:	14
Control:	Sound to light via microphone; DMX; RDM
Fixtures available for:	Light J
Beam angle (1/2 peak):	14°
Color:	Black
Dimensions:	Width: 30.1 cm Depth: 24.7 cm Height: 40.6 cm

Weight:	11.40 kg
DMX channels:	14
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	13 Hz
LED type:	60 W, white
LED number:	1
Beam angle:	14°
Color-wheel:	8 dichroic filters plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	301 x 247 x 406 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x DMH-30/DMH-40

Maximum load:	50 kg
Transport aid:	Castors
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Dimensions:	Width: 72.5 cm Depth: 40 cm Height: 68 cm
Weight:	18.80 kg
Strength:	7 mm
Outside dimensions (W x D x H):	725 x 400 x 680 mm
Inside dimensions (W x D x H):	685 x 360 x 460 mm

EUROLITE TPC-10 Coupler, silver

Maximum load BGV C1 (8-fold):	75 kg
Maximum load WLL (4-fold):	150 kg
Tube diameter sector:	48 - 50 mm
Material:	Aluminum
Color:	Silver
Mounting screw:	M10
Dimensions:	Length: 10 cm Width: 3 cm Depth: 9 cm
Weight:	0.16 kg

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

Secured weight (BGV C1):	Max. 15 kg
Design of the core:	6 x 19 FC
Strength classification:	1770
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strength of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 100 cm Diameter: Ø 0.40 cm
Weight:	0.10 kg
Length weight:	0.0554 kg/m

Scope of delivery:

1 x safety bond
1 x connector