



The article is no longer in our assortment.

Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Bright Uplight with 4 x 8 W 4in1 LED and QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 9,5h depending on program used
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone
- Flicker-free
- With a beam angle of 22°
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- Preprogrammed in Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Mains input and output for power linking up to 8 units
- Integrated automatic charging of the battery and status indicator
- With bracket for floor use
- Cordless, flexible and versatile
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EUROLITE SB-4 Soft Bag M

Black soft bag for up to four devices (Akku UP-4/TL-3 TCL)

- Practical transport bag offers enough space for several lighting effects and accessories
- Large interior, four times divisible and adaptable with foam dividers and pads
- Suitable e.g. for 4 x AKKU UP-4 Spot, 4 x TL-3 TCL Trusslight (41700500) or 3 x AKKU UP-4 Spot QuickDMX (41700540)
- Interior upholstery helps securing and safeguarding the fixtures during transportation
- External pocket stores accessories like cables, clamps, lamps and tape
- Made of easy-care nylon
- Carrying handles

EUROLITE QuickDMX Wireless Transmitter

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x external mains adapter, 1 x USB cable

Technical specifications:

Weight: 15,02 kg

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1 m
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh
Battery pack:	Battery operation up to 9,5h depending on program used Recharging time 3h
Lamp type:	LED lamp

LED:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone
Preprogrammed in:	Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Bracket for floor use
Dimensions:	Width: 16,7 cm Depth: 13,8 cm Height: 18,8 cm
Weight:	3,59 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-4 Soft Bag M

Maximum load:	25 kg
Material:	Textile
Color:	Black
Compartment dimensions:	14 cm x 14 cm x 19 cm
Inside dimensions:	29 cm x 29 cm x 19 cm
Dimensions:	Width: 30 cm Depth: 33 cm Height: 20 cm
Weight:	510 g

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz 5 V DC 1 A
IP classification:	IP20

Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Color:	Silver
Dimensions:	Length: 21,2 cm Diameter: Ø 1,8 cm
Weight:	150 g