

EUROLITE Set LED PFE-50 + Lens Tube 19° + DMX Interface

Handy stage spotlight including lens tube and control modul with DMX interface

Art. No.: 2000056

GTIN:



Features:

- Silent operation
- <p>EUROLITE LED PFE-50 3000K Profile Spot
- <h2 class="featureSatz">Handy stage spotlight with 50 W COB LED in modular construction system, CRI >80</h2>Modular construction kit that can be customized to individual preferences
- 4 shutter blades
- Dimmer and strobe, master/slave functions adjustable via optional DMX interface
- Dimmable
- 1 LED 50 W COB (chip-on-board) warm white (WW)
- The device is cooled by cooling fan
- Control via on/off switch on device; master/slave function
- Fixtures available for LED PC-Control 512; Light Captain; Light`J
- Flicker-free
- With a beam angle of 19°
- Very high color rendering index (CRI)
- With mounting bracket
- Very quiet working noise
- For application areas such as: Trade fair and shop fitting; installation; theater; rental
- Application possibility: Suspended; on stand
- <p>EUROLITE Lens Tube 19° for LED PFE-50
- <h2 class="featureSatz">Lens tube for EUROLITE LED PFE-50 3000 K Profile Spot</h2>Lens tube available with a beam angle of 19°, 26°, 36° or 50°
- With a beam angle of 19°
- <p>EUROLITE DMX-Interface for LED PFE-50
- <h2 class="featureSatz">Control unit with DMX interface for EUROLITE LED PFE-50 3000 K Profile Spot</h2>Adds full DMX functionality to the spotlight
- Dimmer electronic

Logistic

- Strobe effect
- Control via DMX; master/slave function
- 4 digit 7-segment LED display

Technical specifications:

| | |
|-----------------------|---------------------------|
| Weight: | 2.34 kg |
| Noise classification: | Class 0 (no noise at all) |

EUROLITE LED PFE-50 3000K Profile Spot

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 55 W |
| Power connection: | Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided) |
| Power output: | 1 x 3-pin screw plug connector (F) IP |
| Lamp type: | LED lamp |
| Lamp specification: | Dimmable |
| LED type: | 1 x 50 W COB (chip-on-board) warm white (WW) |
| Cooling: | Cooling fan |
| Control: | On/off switch on device; master/slave function |
| Fixtures available for: | LED PC-Control 512; Light Captain; Light´J |
| Projection: | Flicker-free |
| Beam angle (1/2 peak): | 19° (optional) 26° (optional) 36° (optional) 50° (optional) |
| Color temperature: | 3000K |
| Color rendering index (CRI): | 91 Ra |
| Illuminance in Lux (lx): | Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Dimensions: | Length: 30.5 cm Width: 13.4 cm Height: 23.8 cm |
| Weight: | 1.97 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE Lens Tube 19° for LED PFE-50

| | |
|------------------------|---------|
| Beam angle (1/2 peak): | 19° |
| Weight: | 0.25 kg |

EUROLITE DMX-Interface for LED PFE-50

| | |
|----------------|--|
| DMX channels: | 2 |
| Control: | DMX; master/slave function |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 7.1 cm Depth: 3.7 cm Height: 6.4 cm |
| Weight: | 0.12 kg |

Scope of delivery:

1 x mirror ball
1 x spotlight
1 x motor
1 x user manual
1 x remote control
3 x screw
1 x battery
1 x chain

<p>1 x EUROLITE LED PFE-50 3000K Profile Spot</p>1 x spotlight
1 x user manual
1 x power cord
1 x filter frame
1 x gobo holder
1 x terminating plug (power)

<p>1 x EUROLITE DMX-Interface for LED PFE-50</p>1 x device
1 x USB cable
4 x screw