



### Features:

### Logistic

#### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### ALUTRUSS QUADLOCK 6082-2500 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm

- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### **ALUTRUSS QUADLOCK 6082-3000 4-way Cross Beam**

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### **ALUTRUSS QUADLOCK 6082L-30 3-way Corner 90°**

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

#### **ALUTRUSS QUADLOCK End Plate QQGP-Male**

- Trusspipe: 50 mm
- Made in Europe
- **cone**
- M8 thread

#### **ALUTRUSS QUICK-LOCK Spare Pivot with Pin**

QUICK-LOCK set

- Accessories for the robust truss system with QUICK-LOCK
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe

#### **Technical specifications:**

---

Weight: 157.34 kg

---

#### **ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam**

Setup: Easy installation

---

Trusspipe: 50 mm x 2 mm

---

Welding technique: TIG-welding

---

Welding material: AlMg 5

---

Alloy: AlMgSi1 T6

---

Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 200 cm Width: 29 cm Height: 29 cm
Weight:	10.80 kg

#### **ALUTRUSS QUADLOCK 6082-2500 4-way Cross Beam**

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 250 cm Width: 29 cm Height: 29 cm
Weight:	11.85 kg

#### **ALUTRUSS QUADLOCK 6082-3000 4-way Cross Beam**

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 300 cm Width: 29 cm Height: 29 cm
Weight:	14.2 kg

#### **ALUTRUSS QUADLOCK 6082L-30 3-way Corner 90°**

Setup:	Easy installation
Corner angle:	90°
Trusspipe:	50 mm x 2 mm
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 50 cm Width: 50 cm Height: 50 cm
Weight:	7.95 kg

**ALUTRUSS QUADLOCK End Plate QQGP-Male**

Trusspipe:	50 mm
Color:	Alu colored
Weight:	1.45 kg
Thread:	M8 thread

**ALUTRUSS QUICK-LOCK Spare Pivot with Pin**

Trusspipe:	50 mm
Color:	Alu colored
Weight:	0.09 kg

**Scope of delivery:****4 x ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam**

1 x connection set

**4 x ALUTRUSS QUADLOCK 6082-2500 4-way Cross Beam**

1 x connection set

**2 x ALUTRUSS QUADLOCK 6082-3000 4-way Cross Beam**

1 x connection set

**4 x ALUTRUSS QUADLOCK 6082L-30 3-way Corner 90°**

2 x connection set

**8 x ALUTRUSS QUICK-LOCK Spare Pivot with Pin**

2 x splint

2 x bolt