

EUROLITE Set PAR-16 Spot sil + GU-10 230V COB 7W 3000K

PAR-16 housing with GU-10 socket including special lamp for show effect lighting

Art. No.: 20000104

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE PAR-16 Spot GU-10 silver

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Control via plug and play
- For PAR 16

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

OMNILUX GU-10 230V COB 7W 3000K

Special lamp for show effect lighting

- Spare lamp for Eurolite PAR-16 spots: 50850340 EUROLITE PAR-16 Spot GU-10 silver, 50850350 EUROLITE PAR-16 Spot GU-10 black, 50850352 EUROLITE PAR-16 Spot GU-10 white
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:

310 g

EUROLITE PAR-16 Spot GU-10 silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm ² H05SS-F
Cable length:	Approx. 0,4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	Silver
Material:	Aluminum, 1 mm
Slot for spot length:	8 cm x 8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	280 g
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Filter frame	
Shape:	Octagonal
Material:	Aluminum
Dimensions:	Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm
Weight:	10 g

OMNILUX GU-10 230V COB 7W 3000K

Operating voltage:	230 V, 220 - 240 V
Nominal wattage:	7 W
Base:	GU10
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike
Beam angle:	90°
Color of light:	White
Color temperature:	3000K
Lead time:	1 s
Construction:	Reflector; Bi pin

Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	30000 h
Luminous flux:	530 lm
Wavelength:	605 nm
Dimensions (LxD):	72x51 mm
Weight:	30 g
Legal specifications	
Energy efficiency class (A++ - E):	A+