

FUTURELIGHT Set 4x EYE-19 + Case

Art. No.: 20000158

GTIN:



The article is no longer in our assortment.

Features:

FUTURELIGHT EYE-19 RGBW Zoom LED Moving Head Wash

PRO washlight with RGBW color mixing and very large zoom range

- Equipped with 19 x 15 W quadcolor LED with RGBW colors (Osram)
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- Compact housing
- 18, 19, 20 or 98 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution
- Master dimmer
- Motorized zoom with 2 - 50° beam angle
- Each color of the 19 RGBW LEDs can be switched individually
- Color presets
- Preset color temperatures
- Built-in programs
- Animated and static macros
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Switch-mode power supply, automatic power supply adaption between 100 and 240 volts without power selector

Logistic

- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
 - DMX-controlled operation or stand-alone operation with Master/Slave function
 - The scenes can be modified via the Control Board or via an external controller and loaded into the memory
 - Number of scenes can be changed individually
 - Software upload by optional accessories via DMX link
 - Power connection via Neutrik PowerCon jack and included power cable
 - Feed-through output allows to power another device
 - After 8 devices the fixtures must have a renewed connection with the power mains
 - DMX control via every standard DMX controller
 - 19 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
 - PAN angle switchable between 540° and 630°
 - Auto position correction (feedback)
 - Exact positioning (16 bit resolution)
 - Zoom motor driven
 - The device is cooled by temperature-controlled fan
 - Control via RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; sound to light via microphone
 - Flicker-free
 - With a beam angle of 2° - 50°
- device**
- Cordless, flexible and versatile
- Package contents**
- 1 x device

ROADINGER Flightcase 4x EYE-19 / EYE-740

PRO flightcase with castors for 4 x EYE-19 / Eye-740

- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT EYE-19 RGBW Zoom LED Moving Head Wash

| | |
|---------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 300 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 19 x 15 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 265° exact positioning (16 bit resolution) auto position correction (feedback) |

| | |
|--------------------------|---|
| Max. PAN movement: | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0 - 18 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 18; 19; 20; 98 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; sound to light via microphone |
| Projection: | Flicker-free |
| Beam angle: | 2° - 50° |
| Beam angle (1/2 peak): | 2 - 28° |
| Beam angle (1/10 peak): | 8 - 50° |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 2953 lx, 6m: 899 lx Narrow green (G) 3m: 7390 lx, 6m: 2056 lx Narrow blue (B) 3m: 1370 lx, 6m: 388 lx Narrow cold white (CW) 3m: 9604 lx, 6m: 2730 lx Narrow all 3m: 18774 lx, 6m: 5297 lx Wide red (R) 3m: 195 lx, 6m: 60 lx Wide green (G) 3m: 480 lx, 6m: 140 lx Wide blue (B) 3m: 92 lx, 6m: 27 lx Wide cold white (CW) 3m: 599 lx, 6m: 177 lx Wide all 3m: 1198 lx, 6m: 347 lx |
| Housing color: | Black |
| Dimensions: | Width: 34,6 cm Depth: 25 cm Height: 44,5 cm |
| Weight: | 13,35 kg |
| Battery pack type: | 1 x lithium ion 3,7 V, 1,30 Wh |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x EYE-19 / EYE-740

| | |
|--------------------------|---|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |

| | |
|------------------------|---|
| Device compartment: | 37,5 cm x 27 cm x 40 cm |
| Accessory compartment: | 9,5 cm x 55 cm x 40 cm |
| Inside dimensions: | 87 cm x 55 cm x 42,5 cm |
| Dimensions: | Width: 91 cm Depth: 59 cm Height: 66 cm |
| Weight: | 27,90 kg |