

## EUROLITE Set 2x LED PFE-100 RGBW + Case

2x PRO profile spotlight with 100 W 4in1 LED including PRO flightcase

Art. No.: 20000160

GTIN:



**List price: 2200.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED PFE-100 RGBW Profile Spot

PRO profile spotlight, 100 W 4in1 LED (RGBW), zoom, shutter blades

- 1 powerful LED 100 W Filament 4in1 QCL RGBW
- Focus manual
- With a beam angle of 14° - 41°
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Master/slave function
- With Mounting bracket
- For application areas such as: Stage; Installation; video and photography
- Preprogrammed in LED PC-Control 512; Light Captain
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame, 1 x plug (male)

#### ROADINGER Flightcase 2x PFE-100/120

Trunk case with castors, PRO version

- With accessory compartment
- With 2 Device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding

### Logistic

- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Made in Europe
- PENN Hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 50,90 kg

---

### EUROLITE LED PFE-100 RGBW Profile Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	137 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 100 W Filament 4in1 QCL RGBW
Equipment:	Focus manual
DMX channels:	9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle:	14° - 41°
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Lamp life:	50000 h
Luminous flux:	11500 lm
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 61,5 cm Width: 28 cm Height: 42 cm
Weight:	11,10 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	F



Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	PENN Hardware
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Device compartment:	34 cm x 29 cm x 56 cm
Accessory compartment:	69 cm x 10,5 cm x 60 cm
Inside dimensions:	69 cm x 40 cm x 62 cm
Dimensions:	Width: 73 cm Depth: 44,5 cm Height: 88 cm
Weight:	26,30 kg