eurolite®

EUROLITE Set LED KLS Laser Bar FX + M-3 Speaker System Stand

Bar with 2 derbies, 2 spots, white strobe LEDs and laser inklusive speaker stand

Art. No.: 20000172 GTIN: 4026397589108







List price: 498.61 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Laser Bar FX Light Set

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- Laser; multi beam effect; strobe effect; flower effect
- 37 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; party room; mobile djs / entertainer; small rental
- Application possibility: On stand laser
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer

spotlight

- 3 powerful LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
2 spots controlled separately
- With a beam angle of 13°

Logistic

EAN / GTIN: 4026397589108 Weight: 12,55 kg Length: 1.35 m Width: 0.21 m Heigth: 0.58 m Bulky product

light effect

- 3 powerful LEDs 1 W SMD 8072 R/G/B
2 spots controlled separately bar
- 4 powerful LEDs 1 W SMD 8072 cold white (CW)
 LEDs controlled separately Package contents
- 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x foot control, 1 x remote control, 2 x battery, 2 x mounting bracket, 2 x knurled screw, 1 x bag, 2 x washer

OMNITRONIC M-3 Speaker-System Stand

Speaker stand, extendible up to 180 cm, maximum load 30 kg

- Stable speaker stand for mobile use
- Adjustable height
 Package contents
- 1 x stand, 1 x user manual

Technical specifications:

Weight:

12,25 kg

EUROLITE LED KLS Laser Bar FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Device fuse:	5 x 20 mm, F 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 9; 27
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 109 cm
	Depth: 14,5 cm
	Height: 37 cm

Weight:	9,05 kg
Noise classification:	Class 2 (slight noise)
Light effect	
LED type:	3 x 1 W SMD 8072 R/G/B
Spotlight	
LED type:	3 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
Foot control	
Battery:	1 x 9.0 V E block 6LR61 alkaline manganese included
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm
	Green (G) 30 mW 532nm
Bar	
LED type:	4 x 1 W SMD 8072 cold white (CW)
Beam angle (1/2 peak):	7°

OMNITRONIC M-3 Speaker-System Stand

Maximum carrying capacity:	30 kg
Height:	Maximum: 182 cm Minimum: 100 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel (powder-coated)
Color:	Black, painted
Weight:	3,20 kg