

EUROLITE Set 4x LED PMB-8 COB RGB + Case

4x bright bar with 8 x 30 W COB LED, RGB and wide beam angle including PRO flightcase

Art. No.: 20000184

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED PMB-8 COB RGB 30W Bar

Bright bar with 8 x 30 W COB LED, good RGB color mixture, wide beam angle

- Equipped with 8 x 30 W COB LEDs in the colors red, green and blue
- Each LED can be controlled individually
- Rugged housing and an appealing design
- Base for standing installation
- Functions: Static colors, RGB color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via control panel with LCD and four operating buttons
- Neutrik powerCON terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 8 powerful LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- With a beam angle of 60°
- LCD display
- Very quiet working noise
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord

Logistic

ROADINGER Flightcase 4x PMB-8

Trunk case, PRO version

- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Trolley
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 48,45 kg

EUROLITE LED PMB-8 COB RGB 30W Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	8 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	3; 5; 24; 27
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	60°
Beam angle (1/2 peak):	60°
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 88 cm Depth: 15 cm Height: 16,5 cm

Weight:	8,20 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x PMB-8

Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Transport aid:	Trolley
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Device compartment:	18 cm x 16 cm x 84,5 cm
Inside dimensions:	38 cm x 34 cm x 84,5 cm
Dimensions:	Width: 39 cm Depth: 42,5 cm Height: 95 cm
Weight:	15,65 kg