

EUROLITE Set LED KLS-2500 + Case

Art. No.: 20000196

GTIN:









The article is no longer in our assortment.

Features: Logistic

EUROLITE LED KLS-2500 Compact-Light-Set

Bar with 4 spots with 7 x 10 W 5in1 LED each, with 5-pin QuickDMX connector

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- 7 PCL LEDs (RGBAW) per spot
- Comes pre-assembled with practical transport bag
- Movable and tiltable spotlights
- Sound-control via built-in microphone with sensitivity control
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Supports QuickDMX the wireless DMX-system from Eurolite
- Built-in phantom fed socket for QuickDMX receiver (see accessories)
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional foot pedal FP-1
- DMX512 control via regular DMX controller (occupies 28 channels)
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with OLED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and PowerCon input
- 4 IEC outputs for power supply of further devices

- 7 powerful LEDs 10 W high-power 5in1 PCL RGBWA (homogenous color mix)
 spots controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Foot switch (optional)
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain
- With a beam angle of 17,4°

Package contents

- 1 x spotlight

ROADINGER Flightcase KLS Compact Light Sets

PRO flightcase with telescopic handle for 1 x KLS compact light set

- Professional transport solution with extendable trolley for EUROLITE KLS compact light sets
- Suitable for KLS-200, KLS-300, KLS-400, KLS-401, KLS-800, KLS-801, KLS-1001 and KLS-2001
- Compartments for 1 KLS Compact Light Set, 1 foot controller and further accessories
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Interior upholstered with foam
- Three-leg, medium-sized steel ball corners
- 3 hinges
- 2 high-quality butterfly locks
- 3 case handles
- 2 castors
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Trolley
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 27,70 kg

EUROLITE LED KLS-2500 Compact-Light-Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	190,00 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	7 x 10 W high-power 5in1 PCL RGBWA (homogenous color mix)
DMX channels:	2; 3; 4; 7; 20; 23; 28
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Foot switch (optional)
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	17,4°
Beam angle (1/2 peak):	17,4°

Beam angle (1/10 peak):	30,4°
Housing color:	Black
Dimensions:	Width: 1,2 m
	Depth: 6 cm
	Height: 32 cm
Weight:	15,70 kg
DMX channels:	2/3/4/7/20/23/28
DMX connection:	3-pin XLR
QuickDMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED type:	10 W RGBAW (5in1)
Number of LEDs:	28
Beam angle:	28°
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1160 x 60 x 320 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase KLS Compact Light Sets

Maximum load:	50 kg
Transport aid:	Trolley
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	42 cm x 16,5 cm x 12 cm
Inside dimensions:	1,225 m x 26 cm x 12 cm
Dimensions:	Width: 1,265 m
	Depth: 37,5 cm
	Height: 22 cm
Weight:	12,00 kg