



The article is no longer in our assortment.

Features:

EUROLITE Audience Blinder 2x100W LED COB 3200K

Audience blinder, wide beam 2 x 100 W COB LED (warm white)

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 2 powerful LEDs 100 W COB (chip-on-board) warm white (WW)
- Dimmer
- Strobe effect
- Control via DMX
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 60°

ROADINGER Flightcase 8x Audience Blinder 2xCOB

PRO flightcase for 8 x COB audience blinder

Logistic

- For optimal security
- With 8 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 73,15 kg

EUROLITE Audience Blinder 2x100W LED COB 3200K

Power supply:	230 V AC, 50 Hz
Power consumption:	260 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	2 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3200K
Flash rate:	1 - 20 Hz
Equipment:	Dimmer
DMX channels:	1; 2; 4
Control:	DMX
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	60°
Beam angle (1/2 peak):	60°
Housing color:	Black
Dimensions:	Width: 42 cm Depth: 14 cm Height: 24 cm
Weight:	4,50 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	2
LED type:	Array 100 W, white

Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 8x Audience Blinder 2xCOB

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Inside dimensions:	77 cm x 48 cm x 31 cm
Accessory compartment:	10 cm x 43,5 cm x 31 cm
Device compartment:	15,5 cm x 43,5 cm x 20 cm 16 cm x 43,5 cm x 20 cm
Dimensions:	Width: 86,5 cm Depth: 52,5 cm Height: 97 cm
Weight:	37,15 kg